



# HSC-60P

220V~60Hz,1Ph

**Cool Solutions by Airrex!**  
**Approved technology with 37 years experience in the Market! Airrex Spot Cooler 5-Ton 220V~60Hz,1Ph**

Airrex spot coolers operate in air temperatures from 65°F to 115°F. These air conditioners utilize eco-friendly R-410A refrigerant. Airrex spot cooler air conditioners may require a fresh air supply for proper operation. Includes removable, washable air filters for easy maintenance. Thermostatically protected compressor includes high and low pressure warnings. Moves easily on four swivel casters (4 locking). 60,000 BTU Cooling feature two 8" diameter front cold air discharge and 16" diameter top warm air discharge. Optional Warm Air Duct includes ducting and a 2' x 2' ceiling flange for warm air exhausting. ETL listed. Condensate Pump that plugs directly into the portable air conditioner. 1 year warranty and 3 years on compressor.



## Strong Points



Quiet



Thermostats



Intensive Air Conditioning



Movable & Lockable



Energy saving



Automatic



Time Setting



Certification



### Hot Air Exhaust

Automatic fan speed controller  
Operating Range : Up to 115°F



### Spot Cooling

8" Nozzles  
Directed Cooling  
60,000Btu/h



### Condensate Pump

Auto Shut off  
(Built in)



### Applications

Indoor or Outdoor  
Cooling  
Drying



### Digital Controls

Programmable Timer  
Temperature Range: 64°F to 86°F  
Auto Restart



### Mobility

(4) 5" Swivel Casters  
(4) Locking Casters

# HSC-60P 220/1 Specifications



SPECIFICATIONS				Air-Cooled		Fans	Outdoor	Fan Type	-	Centrifugal
				HSC-60P 220/1				Air Volume (High/Low)	CFM	3,020
Capacity Rating Condition	Cooling	(35°C/95°F 40%)	Btu/h	60,000 Btu/h		Sound Level	With Exhaust Duct	High / Low	dB(A)	63
	Heating	(21°C/70°F 50%)	Btu/h	-			Without Exhaust Duct	High / Low	dB(A)	65
	Dehu	Max. (32°C/89°F 80%)	gal/day	90		Air Filter	Type	Indoor	-	Alu+SUS mesh
Nominal (27°C/80°F 60%)		gal/day	71				Outdoor	-	Alu+SUS mesh	
Electrical Characteristics	Voltage	60 Hz	Volts	1 Phase, 220 V~		Condensate	Tank	Capacity	gal	-
	Power Consumption	Cooling	kW	7.2			Auto Pump		-	Included
		Current	Cooling	A	33.0		Refrigerant	Type	-	R-410A
	Heating		A	-		Weight	Net Weight	lbs	628	
	Fuse Size		A	250 V~, 10 A		Dimensions	W x D x H	inch	29 x 54 x 57	
	Min. - Max. Voltage		V	187 - 242 V~		Operating Conditions	Min. - Max.	Cooling	°F	65~115 (18~46°C)
Power Cord	NEMA Plug	-	-				Heating	°F	-	
	Gauge	-	-		Safety Device		High Pressure Switch		○	
	Length	ft	-				Low Pressure Switch		○	
Fans	Indoor	Fan Type	-	Centrifugal			Compressor 3min, Delay Timer		○	
		Cooling Air Volume (High/Low)	CFM	1,850			Thermostat Protector for Compressor		○	
		Heating Air Volume	CFM	-			Fan Motor Protection		○	
		Dehu Air Volume	CFM	1,850			Automatic Full Tank Shut-Off		○	
		Max. External Static Pressure	inchH2O	0.7			Tank Position Dectector		-	
		Max. Equivalent Duct Length	ft	50						
		Type / Size	inch	Duct / 8" (Φ200) x2						

※ Designs and specifications of products are subject to change without prior notice for the improvements. The colors of products may be different due to the printing process.

## Hepa filter optional kit

Optional Filter kit (HSC-36P,60P,70P)



## Ideal Applications for Airrex Portable Air Conditioner



### Industrial Sites

High temperature work sites, car manufacturing plants, ship building yards and steel mills

### Repair Shops

Car repair shops, aircraft workshops, farm machinery workshops, gas stations & parking facilities

### Heat Generating Equipment

Server rooms and machine rooms

### Leisure / Outdoor Event Venues, Farm, & Livestock Ranges

**TEMP-AIR Sales** Office Mailing Address:

[www.tempairsales.com](http://www.tempairsales.com)

2031 Exchange Parkway Ste A, Waco, TX 76712

888-535-8841

[sales@tempairsales.com](mailto:sales@tempairsales.com)